



AquaFlex PRO

Our AquaFlex Pro is now stronger with a new FlexCor platform for installation that's easier than ever!

At 6" wide and 4' long, this ultra-stable plank features the same click-and-lock installation our customers and professional partners adore, with a 5mm overall thickness for the strongest AquaFlex Pro product yet. Breathe easy with zero off-gassing and VOCs and move through life without worries thanks to its 12 mil wear layer and fully waterproof body & backing.

What is AquaFlex? We combined additional PVC, stone, and proprietary resins to create a superior-performing floor. AquaFlex is rigid enough to stop telegraphing, but flexible enough to contour to the natural rolls and imperfections in your floor - 25% more tolerant of imperfections, to be specific, and now the click joints last longer, too.





AquaFlex PRO

FLEXCOR HYBRID TECHNICAL SPECIFICATIONS

Plank Size	5mm x 4' x 6" (1220mm x 180mm)
Sq. ft.; weight per carton	23.64 sq. ft.; 34.27 lbs. per carton
Edge Profile	Micro Bevel
Durability; Warranty	12mil Enhanced Ceramic Bead Urethane; 20 year Residential / 5 year Light Commercial
Core	FlexCor Exclusive (Heat resistance up to 82°C / 180°F)
Residual Indentation	4% used ASTM F1700-13a, ASTM F1914-07 (pass is <8%)
Lock System	Diamond Cut Valinge sides with Innovations I4F drop lock ends
Backing	1mm EVA Foam
Density	1150-1600 kgs/m ³
Expansion Limits	< 0.10mm
STC Rating Foam Backing	71
IIC Rating Foam Backing	72
Water Resistance	Full Waterproof Body and Backing (<3%)
Approved for Radiant Heat	Yes —water type only, NOT electric coil
Finish/Gloss Level	Light Commercial quality matte finish