

# VISUAL COMFORT & Co.

## KSF1061PNGW: LED Flush Mount



### Dimensions:

**Diameter:** 5.0"  
**Width:** 5.0"  
**Height:** 2.38"  
**Weight:** 1.1 lbs.

**Wire:** 8" (color;Black/White)  
**Mounting Proc.:** Cap Nuts  
**Connection:** Mounted To Box  
**Bulb Type:** Array  
**Bulb Type:** Integrated  
**Volts:** 120  
**Watts:** 9  
**Watts Consumed:** 9  
**Watts Rated:** 9  
**Hours Rated:** 50000  
**Lumens:** 700  
**Bulb Temp:** 3000 °K  
**CRI:** 90

### Bulbs:

1 - LEDIntegrated Modules 9.0w Max. 120v included

### Features:

- This product is dimmable.
- This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.
- Meets Title 24 energy efficiency standards
- Integrated LED fixtures that meet the high efficacy LED standards set forth in Title 24 and are listed in the California Energy Commission Appliance database.

**Collection:** Monroe

Featured in the decorative Monroe collection

Milk Glass shade

**UPC #:**014817620757

**Finish:** Polished Nickel (PN)

### Material List:

1 Body - Steel - Polished Nickel  
1 Accents - Steel - Gloss White

### Safety Listing:

Safety Listed for Damp Locations  
Safety Listed for Damp Locations

### Instruction Sheets:

Trilingual (English, Spanish, and French) (MONROE-FLUSHMOUNT)  
Trilingual (English, Spanish, and French) (ksf1051 ksf1061 ksf1072)

### Shade / Glass / Diffuser Details:

Part	Material	Finish	Quantity	Item Number	Length	Width	Height	Diameter	Fitter Diameter	Shade Top Length	Shade Top Width	Shade Top Diameter
Shade	Glass	Milk	1				1.0	4.5				

### Backplate / Canopy Details:

Type	Height / Length	Width	Depth	Diameter	Outlet Box Up	Outlet Box Down
Canopy	1.5			5.0		

### Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Fr. Class	UPS Ship
Individual	KSF1061PNGW	1	014817620757	8.5	9.1	7.2	0.32	1.35	0	Yes
Master Pack	KSF1061PNGW	0	10014817620754							No
NJ Pallet		200		48.0	40.0	76.0	84.44	270.0		No
NV Pallet		200		48.0	40.0	76.0	84.44	270.0		No